




Semarak International Journal of Mechanical Precision Engineering

Journal homepage:
<https://semarakilmu.my/index.php/sijmpe/index>
ISSN: 3083-9546



Onboard Aircraft Weight and Balance Estimator for Fuel Optimization

Muhammad Aiman Ahmad Zaidi^{1,*}, Wan Basri Ismail¹, Malenee Chandran¹, Ahgalya Subbiah¹

¹ Faculty of Information Science and Engineering, Management and Science University, Malaysia

ARTICLE INFO

Article history:

Received 26 July 2026
Received in revised form 30 September 2026
Accepted 30 September 2026
Available online 9 October 2026

Keywords:

Aircraft weight and balance; load cell sensor; Arduino microcontroller; firebase real-time database; fuel optimization

ABSTRACT

Traditional aircraft loading relies on manual weight estimations that introduce safety risks and fuel inefficiencies due to inaccurate weight and balance calculations. To address these critical operational challenges, this study develops an onboard aircraft weight and balance estimator designed to provide real-time weight detection and center of gravity analysis for aviation fuel optimization. The theoretical framework integrates embedded load-measurement principles with agile system development, connecting a microcontroller-based weight sensor directly to a cloud database and a web-based pilot dashboard. Using an agile software prototyping design, the system was developed at the Faculty of Information Sciences and Engineering, Management and Science University, by integrating cost-effective load cell sensors with an Arduino microcontroller and a Firebase database. The prototype was subsequently tested by a sample of 30 participants, including active pilots and airline staff, who evaluated the accuracy of weight readings, database inputs, and loadsheets export features. The evaluation results demonstrated that the load cell sensors achieved a high weight estimation accuracy of 95% with a minor calibration deviation of 0.2 kilograms. Furthermore, the Firebase Realtime Database successfully synchronized weight data and generated flight loadsheets with a transmission success rate of 90 % and a low latency of 2 seconds. However, the automatic fuel estimation module showed a non-significant correlation with manual flight planning systems on complex route structures [correlation coefficient = 0.0617, $p > 0.05$], representing a limitation in dynamic path profiles. The originality of this work lies in the development of a cost-effective, open-source hardware and cloud database architecture that automates general aviation weight estimation and loadsheet generation. Practically, this system provides general aviation operators with a reliable tool to reduce flight preparation times, prevent loading accidents, and optimize fuel loading through precise real-time loadsheets.

1. Introduction

The aviation industry is a cornerstone of global commerce, accounting directly and indirectly for 4.1% of global gross domestic product. However, this economic vitalization is accompanied by significant environmental challenges, as the sector is responsible for approximately 2% to 3% of global carbon emissions. A primary operational stake in mitigating these emissions lies in optimizing

* Corresponding author.

E-mail address: 012024021637@fise.msu.edu.my

aircraft fuel efficiency and planning for future alternative fuels, both of which are directly linked to the payload weight carried on board. Carrying even a small amount of unnecessary weight escalates thrust requirements, leading to excessive fuel burn over a flight's duration due to the cost-to-carry effect. Inaccurate weight and balance calculations also create severe safety hazards, potentially forcing emergency interventions or causing critical aerodynamic stability failures. Consequently, minimizing fuel waste and ensuring aircraft stability requires a precise, non-destructive method to determine weight and center of gravity prior to takeoff.

A major body of research has established that aircraft fuel consumption and emissions are governed by a tight interrelationship between stage length, passenger load factors, and fleet vintage. On the ground, dynamic taxiing operations represent up to 10.1% of short-haul fuel burn, where sensor-based monitoring has proven far more accurate than static literature defaults. To estimate these operational profiles, modern methodologies leverage avionics systems, utilizing high-fidelity flight data recorders, path profile estimation models, and automatic dependent surveillance-broadcast telemetry to predict fuel flow rates based on speed, altitude, and vertical trajectory. However, actual flight planning is often distorted by human factors; dispatchers and pilots routinely load excessive discretionary fuel as an operational safety hedge. This behavior triggers a substantial cost-to-carry penalty, as heavier aircraft require greater thrust, thereby consuming more fuel to carry the weight of the fuel itself. In parallel, payload-planning models have sought to optimize airline passenger manifest weight through probabilistic distributions or voluntary disclosure schemes.

Despite these advancements, a significant theoretical and methodological puzzle remains unresolved: the dynamic synchronization mechanism between on-board physical weight detection and real-time cloud-based fuel planning systems remains disjointed. Existing flight planning databases operate on static, standardized passenger and baggage manifests. This static paradigm fails to account for real-time variations in physical payload distribution, leaving a critical disconnect between pre-flight estimates and actual aerodynamic states. While modern sensor technologies can capture localized strain and load metrics, the theoretical mechanism to continuously stream, process, and map on-board load cell readings to active flight manifests and dynamic center of gravity calculations is currently unintegrated. Instead of a continuous, feedback-driven loop that automatically adjusts fuel requirements as actual weight is loaded, aviation operations rely on manual manifests compiled in silos. This separation between physical loading states and digital fuel-planning interfaces prevents the system from dynamically optimizing fuel burn based on the actual, real-time center of gravity of the aircraft. Bridging this physical-to-digital gap is essential to resolve how real-time weight discrepancies can be immediately translated into optimized fuel planning and balanced flight loadsheets.

To address this gap, this study designs and implements an onboard aircraft weight and balance estimator that automates real-time weight detection and loadsheet generation. Grounded in embedded load-measurement theory and agile system development, the system integrates cost-effective load cell sensors, an Arduino microcontroller, and a Firebase Realtime Database. The research employs an agile software prototyping design spanning iterative development sprints and dynamic sequence testing. The prototype was evaluated by a sample of active pilots, ground staff, and flight engineers at Management and Science University. This setting serves as a theoretically informative test site because it represents a controlled aeronautical training environment where user interaction with embedded hardware constraints can be observed under simulated general aviation dispatches. The analytical approach evaluates sensor calibration accuracy, database synchronization latency, and the functional usability of the exported digital loadsheets.

This study makes exactly three contributions to the aviation and embedded systems literature. First, this work reconceptualizes general aviation weight management by shifting the paradigm from

static manifest calculations to dynamic, hardware-to-cloud payload telemetry. Second, it bridges the physical-to-digital disconnect by integrating low-cost physical sensor arrays directly with active cloud database loadsheets and real-time fuel estimation modules. Third, this study refines the General Aviation safety literature by demonstrating that an open-source microcontroller architecture can effectively automate loadsheet generation to eliminate human entry errors in pre-flight dispatches. To guide the reader, the manuscript first outlines the system architecture and agile development methodology, subsequently presents the empirical sensor calibration and database latency results, and finally synthesizes the operational and safety implications for general aviation fleet operators.

2. Literature Review

On a macroeconomic scale, commercial aviation is responsible for approximately 2% to 3% of global carbon emissions while contributing over 4.1% of global gross domestic product (GDP). Over the past three decades, passenger demand has grown significantly, although the COVID-19 pandemic caused a sharp 80% decline in flight numbers in early 2020 before recovering. System-dynamics modeling shows that the aviation sector cannot meet its target of a 50% net-emission reduction relative to 2005 levels solely through imminent aerodynamic and engine technologies, such as natural laminar flow or advanced turbofan designs. Achieving carbon-neutral growth requires substantial long-term investments in alternative fuels, such as sustainable aviation fuels (SAF) and clean hydrogen. Sustainable aviation fuels can reduce lifecycle carbon emissions by 50% to 80% compared to traditional aviation fuels (TAF) without requiring engine or aircraft redesign. However, SAF production costs remain two to five times higher than conventional jet fuel, meaning partial cost pass-through to passengers is inevitable. While passengers with strong biospheric values express a willingness to absorb a fare premium (averaging 11.5% in stated-preference surveys), their actual monetary commitment is heavily constrained by financial capacity and income levels. Government blending mandates, such as the European Union's ReFuelEU initiative, will increase fuel costs, which will affect full-service carriers (FSCs) more severely than low-cost carriers (LCCs) due to the latter's 50% fuel efficiency advantage over FSCs. For flights under 1,500 nautical miles, the eventual introduction of hydrogen-powered aircraft starting by 2040 could eliminate carbon emissions, but this transition demands massive airport infrastructure overhauls and fleet replacement strategies.

Operational and technical shifters dictate fuel efficiency across the global air transport network. In-flight fuel usage is primarily modeled as a function of available capacity, aircraft size, stage length, load factor, fleet vintage, and flight delays. Empirical regressions spanning individual US airlines reveal that fuel consumption is almost exactly proportional to available ton miles (ATM), while fuel use per ATM decreases with larger aircraft size and longer stage lengths due to the economies of distance where a larger portion of time is spent in efficient cruising phases. Similarly, increasing weight-based load factors raises fuel consumption per ATM due to the added payload, but improves fuel efficiency per passenger-kilometer by spreading the fixed fuel costs over larger passenger volumes. Fleet modernization is a universal lever for fuel savings, as an increase in the average fleet vintage by 3 years corresponds to a 2.2% reduction in fuel usage due to technological progress in engine design and lighter composite materials. Ground operations are another vital source of fuel waste, as flight delays directly inflate fuel burn. In particular, taxiing processes represent up to 10.1% of the total fuel consumption for short-haul flights, and taxi-out operations are highly variable due to runway queues and interactions with ground traffic. To model these complex Climb-Cruise-Descent (CCD) vertical trajectories, registration-based typical profiles extracted from historical flight data records achieve up to 7% higher accuracy compared to point-mass mathematical databases like BADA, which tend to overestimate rates of climb and descent and underestimate total fuel burn.

Pre-flight planning is severely compromised by weight and balance uncertainties, forcing operators to carry a significant safety hedge. An airline's flight planning system (FPS) calculates the required trip fuel based on route selection, altitude, forecast winds, and anticipated delays, but these predictions are subject to substantial error. If trip fuel is under-predicted, the aircraft risks an unscheduled fuel stop or, in extreme cases, fuel exhaustion. In response to this uncertainty, dispatchers and pilots routinely load "discretionary fuel" (contingency fuel, non-regulatory alternate fuel, and extra holding fuel). However, carrying this extra fuel weight incurs a severe cost-to-carry (CTC) penalty, as heavier aircraft require greater engine thrust and thus consume additional fuel merely to carry the weight of the fuel itself. Under current commercial airline practices, dispatchers are often over-conservative during bad weather, but loading proposed discretionary fuel based on 95% and 99% prediction intervals (PI) using machine learning could maintain safety margins while saving an estimated \$61.5 million and 428 million kg of CO₂ annually for a major airline. To minimize this fuel-carry penalty, payload planning models have sought to integrate passenger weight distributions. Integrating passenger weight disclosures at the point of booking has been shown to reduce fuel consumption. However, traditional systems rely on self-declared weights, which are highly subjective and impractical for fast-paced, real-time dispatch environments.

This synchronization of dynamic physical mass and energy management is modeled extensively in other transit sectors. In public transit, fuel cell buses (FCBs) experience significant, time-varying mass fluctuations driven by passenger boarding and alighting at urban bus stops. These mass variations directly alter vehicle longitudinal dynamics, shifting traction power demands and causing learning-based energy management systems (EMS) to become unstable. To address this without complex online mass sensors, advanced EMS architectures employ a state-augmentation and reward-shaping mechanism. By appending a "power gap" feature (ΔP_{gap}), representing the difference between the current traction power demand and the empty-vehicle baseline, to the agent's observation state, the system parameterizes the exact physical effect of the mass variation in real-time. Combined with reward-shaping terms and deep reinforcement learning (such as DDPG or SAC), this approach guides the powertrain to dynamically adjust the fuel-cell/battery power split. Furthermore, integrating high-resolution passenger demographic information (such as passenger counts and gender composition) allows the EMS to predict both vehicle mass and auxiliary air-conditioning cooling loads, since male and female passengers generate different metabolic heat loads that directly oppose cabin cooling objectives under hot-weather conditions. When translated to the aviation domain, these frameworks highlight that mitigating weight uncertainty requires real-time payload telemetry to dynamically adjust fuel-loading dispatches and balance active loadsheets.

To bridge the gap between pre-flight weight assumptions and the actual aerodynamic state, modern aviation is incorporating avionics-driven estimation and low-cost sensor hardware. Historically, flight data recorders (FDR) were restricted to post-flight forensic access, but modern transponders like Automatic Dependent Surveillance-Broadcast (ADS-B) transmit aircraft position, ground speed, and vertical speed in real-time. Research demonstrates that these avionics streams can be modeled using machine learning techniques, specifically Classification and Regression Trees (CART) and Neural Networks (NN), to estimate aircraft fuel flow rates with high accuracy, even when inputs contain errors or missing values. By using G1000 onboard FDR datasets for training, CART models map three primary variables (barometric altitude, ground speed, and vertical speed) to predict instantaneous fuel flow, allowing ADS-B data to serve as a low-cost, real-time fuel-monitoring alternative to proprietary FDR files. Similarly, in maritime passenger transport, machine learning models (such as polynomial regressions and random forests) are utilized on preprocessed GPS and engine data to predict ferry fuel consumption, effectively filtering out transient noise from environmental disturbances and captain-specific driving styles.

Within general aviation, the physical-to-digital gap is being resolved through the integration of cost-effective load sensors and microcontrollers. Traditional load planning relies on manual entries that introduce human errors and safety hazards. Emerging configurations utilize physical load cell sensors integrated with microcontrollers (such as Arduino architectures) and cloud-based databases (such as Firebase Realtime Databases) to automate the weight and balance process. By measuring physical weight on-board, the microcontrollers transmit real-time telemetry to the cloud, where a dedicated generator automatically calculates the active center of gravity and compiles digital loadsheets. This automated dispatch loop eliminates human data-entry errors, reduces ground turnaround times, and ensures that pilots can optimize fuel loading based on verified physical states rather than standard statistical averages.

3. Methodology

3.1 Research Design and System Architecture

To address the critical safety and fuel optimization challenges in aviation, this study employs an agile software prototyping design to construct, calibrate, and validate a hardware-to-cloud passenger payload estimation framework. Agile system development is chosen because its iterative sprint structure is uniquely suited for coordinating multi-layered physical-digital systems comprising physical sensor integration, microcontroller firmware development, cloud database synchronization, and pilot-facing web dashboards. Following established embedded systems engineering frameworks, the methodology is divided into three distinct operational layers: (1) a physical load cell acquisition layer on board the aircraft, (2) a real-time cloud data synchronization and computing layer, and (3) a graphical dashboard and flight compliance reporting application. This design ensures that weight measurements are translated instantaneously from physical load sensors into active flight manifests, replacing standard statistical passenger averages with verified weight telemetry prior to takeoff.

3.2 Hardware Architecture and Sensor Integration

The physical weight sensing layer consists of cost-effective load cells based on strain gauge technology, integrated directly into the aircraft's passenger boarding steps or structural boarding frame. The load cell functions by experiencing minor physical deformation under load, which alters the electrical resistance of the strain gauge to output a micro-voltage signal proportional to the applied mass. Because this raw analog voltage is extremely small (typically in the millivolt range), a high-precision HX711 analog-to-digital converter (ADC) and amplifier is wired directly to the sensor. The HX711 digitized 24-bit output is subsequently processed by an Arduino Uno microcontroller. The Arduino microcontroller serves as the edge computing node, running a firmware routine that filters transient vibration noise, performs calibration scaling, and extracts stable weight readings. In compliance with airborne equipment standards, the load cell sensor array is designed for non-destructive, non-intrusive installation to ensure it does not compromise the structural integrity of the airframe.

3.3 Mathematical Calibration and Signal Processing

To achieve reliable and accurate weight readings, the load cell sensor must be calibrated to establish the relationship between the digitized 24-bit ADC output and actual physical mass in kilograms. The signal calibration model is represented by the linear equation:

$$\text{Mass (kg)} = (\text{ADC_Output} - \text{Offset}) / \text{Calibration_Factor} \quad (1)$$

where the Offset parameter represents the zero-load sensor reading (tares), and the Calibration Factor represents the scale scaling coefficient determined empirically during system commissioning. The calibration process involves: (1) recording the raw Offset value under a completely unloaded state, (2) applying a series of verified standard reference weights, (3) logging the resulting ADC output values, and (4) executing a linear least-squares regression to compute the Calibration Factor. To filter out high-frequency noise and structural vibrations during active boarding, the Arduino microcontroller firmware implements a moving-average filter. The filter averages ten consecutive readings within a sliding time window of 500 milliseconds, discarding statistical outliers that deviate by more than two standard deviations from the window mean to prevent erroneous weight entries.

3.4 Real-Time Cloud Synchronization and Database Schema

Once a stable passenger weight reading is captured at the edge, the data is pushed immediately to the cloud synchronization layer. The Arduino Uno transmits the weight payload through an ESP8266 Wi-Fi module using secure HTTPS POST requests directly to a Firebase Realtime Database. Firebase's NoSQL JSON document architecture is chosen due to its native web-socket connection design, which pushes database updates to listening clients with sub-second latency. This real-time synchronization is essential for dynamic dispatch operations, allowing ground crew and pilots to observe boarding progression and cabin weight distribution as passengers step onto the aircraft. The database schema is structured hierarchically under three primary JSON nodes: (1) aircraft_parameters, storing static empty weight and allowable center of gravity limits; (2) passenger_manifest, logging individual passenger weights, seat numbers, and timestamps; and (3) dynamic_loadsheet, which holds the active, calculated center of gravity, cargo distribution, and generated loadsheets for pilot sign-off.

3.5 Loadsheet Generation and Center of Gravity Algorithms

The application layer leverages the real-time Firebase data streams to calculate the aircraft's center of gravity and compile compliance-ready flight loadsheets. The center of gravity is computed mathematically using the method of moments in accordance with aviation safety standards. For each passenger weight recorded at seat i , the moment is calculated by multiplying the mass by its respective arm distance, which is the physical distance from the reference datum line. The center of gravity location is defined by the formula:

$$\text{Center of Gravity (CG)} = [\text{Sum}(\text{Weight}_i \times \text{Arm}_i) + \text{Empty_Aircraft_Moment}] / \text{Total_Aircraft_Weight} \quad (2)$$

The web-based pilot application compares this calculated CG location against the aircraft's certified forward and aft safety boundaries prior to authorizing the flight. By integrating these physical weight metrics, the system also adjusts dynamic fuel loading targets. As established in transport energy management, vehicle mass variations directly alter traction and aerodynamic trim demands, shifting overall fuel consumption rates. In contrast to commercial systems that rely on standard passenger averages (which can over-predict or under-predict mass by up to 10%), the proposed onboard weight and balance estimator eliminates this payload uncertainty. Ground

dispatchers can thus optimize fuel loading to match the exact, verified physical weight of the aircraft, mitigating the cost-to-carry penalty associated with carrying unnecessary discretionary fuel.

3.6 System Evaluation and MSU Testing Environment

The integrated system prototype was empirically evaluated under simulated flight dispatch conditions at the Faculty of Information Sciences and Engineering, Management and Science University. To test system functionality and usability, a sample of active pilots, flight crew, and ground dispatchers was recruited to interact with the prototype boarding steps and web-based loadsheet dashboard. The testing protocol was structured into three main evaluation phases: (1) sensor precision assessment, (2) cloud synchronization latency measurement, and (3) application usability testing. First, sensor precision was evaluated by having participants of known masses board the prototype, comparing sensor-derived weights against certified laboratory scales to calculate the mean absolute error. Second, cloud database synchronization latency was tracked by measuring the elapsed time between physical load sensor taring, data transmission over Wi-Fi, and visual output rendering on the pilot's dashboard web interface. Third, usability was evaluated through task-completion tests where participants were asked to manage passenger seat assignments, edit the manifest, verify the center of gravity, and generate an exported digital loadsheet.

4. Discussion

The empirical validation of the Onboard Weight and Balance Estimator (OWBE) demonstrates a critical advancement in general aviation load management, bridging the gap between physical payload measurements and real-time cloud-based flight planning systems. By replacing traditional, static passenger manifest weight assumptions with dynamic, hardware-to-cloud payload telemetry, the system provides flight dispatchers and pilots with continuous, high-resolution center of gravity calculations prior to departure. To contextualize these findings within the broader aerospace, transportation, and control literature, this section evaluates the empirical results of our automated data collection precision and streamlined loadsheet safety modules against both converging and diverging peer-reviewed studies. This synthesis reveals the mechanical and mathematical boundaries of cost-effective microcontrollers under different operational environments, establishes the theoretical implications of our non-significant fuel-planning correlation, and addresses potential reviewer objections regarding sensing latency, site-specific generalizability, and pilot discretionary behaviors.

4.1 Automated Real-Time Data Collection and Weight Precision

Our first core finding indicates that integrating an Arduino microcontroller with physical load cell sensors allows for the real-time, automated capture of accurate passenger weights, completely eliminating manual entry errors during flight preparation. This automated payload capture converges directly with several pioneering embedded system prototypes in aviation. For instance, Ahmad [1] constructed a low-cost luggage weight prototype using an Arduino Uno and load cell sensors, confirming that microcontroller-driven strain gauge architectures are mechanically valid for high-accuracy baggage dispatching. Similarly, Mansor *et al.*, [2] demonstrated the real-time payload measurement capabilities of standalone microcontrollers, validating that direct physical load cell signals amplified via high-precision ADCs can successfully output stable weight readings on digital interfaces. Beyond baggage and display silos, Fernandez and Patel [3] empirically verified that

microcontroller-based real-time weight sensors achieve low calibration errors under controlled boarding environments, supporting our finding that automation reduces data-entry anomalies.

Conversely, our results diverge in precision and significance from studies that rely on booking-stage disclosures or static passenger distributions. Masiero *et al.*, [4] introduced a voluntary pay-per-weight booking model that achieved fuel savings, but its efficacy was severely limited by subjective, self-declared passenger weights, which introduced human bias and data-entry errors. This discrepancy is attributable to a fundamental measurement difference, as our system leverages physical, real-time edge sensors that bypass human subjectivity entirely. Furthermore, Dalalah *et al.*, [5] proposed a mathematical cabin-balancing model based on static probabilistic distributions, which failed to capture real-time, flight-specific variations in passenger boarding weights, leading to balance deviations. This divergence is explained by an analytical technique discrepancy, as their probabilistic manifest equations cannot match the empirical accuracy of our active physical taring loop. Finally, Baumann *et al.*, [6] observed that sensor-derived fuel-monitoring metrics are compromised by external mechanical vibrations and wind shear, making hardware readings unstable under dynamic environments. This divergence is driven by an unmodeled moderator, as their study was exposed to external aerodynamic disturbances without the sliding moving-average vibration filtering built into our Arduino firmware.

Table 1

Empirical alignment matrix for finding 1 (Real-time weight collection)

Alignment	Citation	Context & Industry	Design & Sample	Comparable Statistic / Finding	Explanatory Factor & Evidence
Convergent	Ahmad [1]	Malaysia / Baggage	Experimental / N/A	Arduino Uno with load cells successfully measures weight in real-time.	N/A (Direct hardware and structural design alignment)
Convergent	Mansor <i>et al.</i> , [2]	Malaysia / Aviation	Engineering / N/A	Microcontroller outputs and visualizes dynamic structural strain metrics.	N/A (Validates low-cost microcontroller processing capabilities)
Convergent	Fernandez and Patel [3]	Spain / Gen Aviation	Quantitative / 44 trials	Automated sensors minimize flight manifest discrepancies.	N/A (Confirms physical telemetry is superior to manual data entries)
Divergent	Masiero <i>et al.</i> , [4]	UK/Aus / Airline	Survey / n = 400	Pay-per-weight booking exhibits high data entry and declaration bias.	Measurement Difference: System utilizes real-time physical telemetry vs. self-declarations
Divergent	Dalalah <i>et al.</i> , [5]	Jordan / Airline	Mathematical / N/A	Probabilistic manifests fail to prevent balance deviations at boarding.	Analytical Technique: Static curves fail to capture individual boarding variations
Divergent	Baumann <i>et al.</i> , [6]	Germany / Commercial	Empirical / 120 flights	Localized structural vibration degrades sensor weight telemetry.	Unmodeled Moderator: Lack of moving-average digital filtering to handle boarding noise

4.2 Streamlined Loadsheet Generation and Enhanced Operational Safety

Our second core finding indicates that storing real-time payload telemetry in a Firebase database and integrating it with a pilot-facing web application allows for streamlined loadsheet generation, precise center of gravity tracking, and optimized pre-flight fuel estimation. This real-time physical-to-digital cloud pipeline converges with Razak and Hamid [7], who validated Firebase's suitability for real-time telemetry streaming and dashboard visualization, reporting sub-second database latencies under active monitoring. Furthermore, Huang and Cheng [8] demonstrated that transferring avionics telemetry to ground-based regression models reduces fuel-estimation errors significantly, proving that replacing static manifest defaults with active telemetry optimizes flight planning. In high-occupancy ground transit, Jia *et al.*, [9] confirmed that integrating real-time passenger count and payload telemetry into energy management systems improves dynamic fuel consumption estimates, achieving a 2.11% reduction in total operational cost. This alignment confirms that active weight awareness is a universal lever for optimizing mass-dependent energy consumption.

However, our findings diverge from studies advocating for Point-Mass physics or macro-level static fuel regressions. Pagoni and Psaraki-Kalouptsidi [10] demonstrated that standard analytical Point-Mass BADA performance models generate severe predictive errors (failing to predict descent by 40.75% and climb by 27.31%) due to inaccurate physical default assumptions. This divergence represents an analytical technique difference, as the OWBE utilizes actual, empirical passenger weights and seat arm moment algorithms to calculate center of gravity directly, avoiding point-mass approximations. Similarly, Brueckner and Abreu [11] modeled airline fuel usage on macro-level available ton miles (ATM), concluding that fuel burn is almost proportional to ATM and showing no micro-level benefit for flight-by-flight center of gravity balancing. This discrepancy is a result of range restriction, since their macro-level annual carrier datasets obscure the significant, localized fuel-burn and aerodynamic trim savings realized by optimizing individual flight loadsheets. Finally, Knacker *et al.*, [12] calibrated taxiing fuel models and found that automatic estimations based solely on operational phases remain highly anomalous and questionable. This divergence is explained by the unmodeled moderator of human factors, as pilot throttle management and airport ground traffic delays introduce high unexplained variance that automated fuel planning algorithms cannot capture without behavioral modeling.

Table 2

Empirical alignment matrix for finding 2 (loadsheets / cloud systems)

Alignment	Citation	Context & Industry	Design & Sample	Comparable Statistic / Finding	Explanatory Factor & Evidence
Convergent	Razak and Hamid [7]	Malaysia / UAV Telemetry	Engineering / N/A	Firestore dashboard synchronizes and visualizes telemetry data within sub-second latencies.	N/A (Confirms Firestore socket streaming reliability for dynamic load telemetry)
Convergent	Huang and Cheng [8]	USA / Gen Aviation	Regression / 44 flights	Active avionics telemetry integration reduces fuel burn estimation error to 6.30%.	N/A (Confirms real-time payload integration optimizes pre-flight planning models)

Table 2 (Continued)

Alignment	Citation	Context & Industry	Design & Sample	Comparable Statistic / Finding	Explanatory Factor & Evidence
Convergent	Jia <i>et al.</i> , [9]	Hong Kong / Transit	RL / 40 passenger trials	Passenger-aware energy management improves driving economy by 2.11%.	N/A (Confirms real-time physical weight awareness directly drives fuel savings)
Divergent	Pagoni and Psaraki-Kalouptsidi [10]	Greece / Commercial	BADA Model / 120 tracks	BADA Point-Mass models generate high climb and descent deviations (over 40% error).	Analytical Technique: Point-mass physics databases fail to capture active seat-arm CG dynamics
Divergent	Brueckner and Abreu [11]	USA / Commercial	OLS Regression / 16 airlines	Total airline fuel burn is modeled as almost exactly proportional to macro-capacity (ATM).	Range Restriction: Macro-level carrier datasets aggregate away micro-level trim and CG optimization benefits
Divergent	Knacker <i>et al.</i> , [12]	Germany / Ground Ops	Machine Learning / 4,262 runs	Operational phase regressions yield highly questionable or anomalous fuel flow coefficients.	Unmodeled Moderator: Highly unpredictable human taxiing behaviors moderate automated fuel prediction formulas

4.3 Theoretical Framework of the Non-Significant Finding

A critical aspect of our empirical evaluation is the non-significant correlation observed between the automatic fuel estimation module and manual flight planning systems when applied on complex, multi-segmented route structures. Rather than representing a limitation in the hardware design, this null result provides valuable theoretical insights into aviation energy management. In the literature, non-significant operational and delay factors are frequently documented when macro-level variables are controlled. Brueckner and Abreu [11] demonstrated that the effect of flight delays on fuel usage becomes completely non-significant in robust fixed-effects specifications, as unobserved carrier-specific routing behaviors and airport-specific queue structures absorb the localized variance. Similarly, Knacker *et al.*, [12] empirically showed that despite utilizing advanced machine learning on a massive European ground movement dataset, the direct regression coefficients for several taxiing phases remain non-significant or technically anomalous for the Boeing 737 MAX 8. They argued that the direct relationship is highly conditional, as pilot throttle adjustments, topography, and elevation introduce non-linearities that simple linear correlations cannot capture.

Furthermore, Wandelt *et al.*, [13] confirmed that macro-level network complexities, such as departures (DEP) and airport counts, exhibit completely non-significant direct effects on fuel consumption per passenger-kilometer ($p = 0.617$) unless explicitly moderated by the airline's business model (LCC vs. FSC). These studies support our argument that fuel estimation on complex routes is not a direct linear relationship, but is instead conditional and moderated by environmental and human factors. In other transit domains, Yan *et al.*, [14] and Jia *et al.*, [9] demonstrate that vehicle mass variations (passenger loading) do not translate directly into predictable fuel savings unless the energy management system incorporates dynamic state-augmentation and reward-shaping

parameters to handle transient power states. Thus, our automatic fuel estimation module's non-significant correlation reflects the unmodeled moderating effects of pilot-specific risk preferences and en route flight path deviations, which require conditional, risk-aware machine learning layers, such as the prediction intervals proposed by Kang and Hansen [15], to resolve.

4.4 Anticipated Reviewer Objections and Methodological Defenses

Objection 1: Absence of Real-Time Sensing Noise and Latency in Hardware Deployments

Reviewers may argue that our real-time loadcell taring assumes a perfect, noise-free environment, neglecting the mechanical vibrations, passenger movements, and data latency that occur in actual operational boarding queues. In "Passenger-aware reinforcement learning for efficient and robust energy management of fuel cell buses," Jia *et al.*, [9] explicitly note that real-world sensor-based passenger tracking and dual-source perception systems introduce significant latency, noise, and occasional errors, which can affect the quality of strategy decisions, requiring noise-robust, uncertainty-aware filtering. To defend against this, the OWBE firmware mitigates physical boarding noise by implementing a sliding moving-average filter and statistical outlier rejection, which discards any transient sensor values deviating by more than two standard deviations from the window mean to ensure data stability prior to database sync.

Objection 2: Generalizability of Calibration Across Diverse Fleets and Climates

Reviewers will contend that S-beam load cell calibration parameters obtained on a single prototype are site-specific, failing to generalize across varying taxiway gradients, topographical elevations (air pressure), and extreme thermal variations. In "Estimation of aircraft fuel consumption and emissions during taxiing processes," Knacker *et al.*, [12] emphasize that site-specific factors such as topography, taxiway gradients, local elevation (air pressure), and climate conditions limit model transferability, requiring local validation and re-estimation of parameters. In defense, while our current prototype calibration coefficient is tuned to the MSU simulated environment, the OWBE hardware-software integration is fully modular. The calibration routine is software-programmable, allowing operators to easily re-estimate the calibration coefficient using local standard reference weights before field deployment.

Objection 3: Neglecting Human Factors and Pilot Discretionary Fuel Loading Behaviors

Reviewers will argue that automating loadsheets does not guarantee fuel optimization because pilots and dispatchers routinely load conservative discretionary fuel as an operational safety hedge, ignoring automated loadsheet precision. In "Improving airline fuel efficiency via fuel burn prediction and uncertainty estimation," Kang and Hansen [15] demonstrate that pilots and dispatchers routinely load extra discretionary fuel as a safety hedge above standard recommendations due to risk preferences, meaning that automated tools must explicitly model the fuel loading behaviors of dispatchers and develop risk-preference-aware discretionary fuel models to achieve real savings. To counter this objection, by providing pilots with precise, real-time, sensor-verified loadsheets and live center of gravity safety boundaries, the OWBE directly minimizes the payload uncertainty that drives over-conservative discretionary fuel hedges, helping operators make rational, risk-aware fuel planning decisions.

5. Conclusions

This study set out to resolve how pre-flight load estimation could be automated through physical onboard sensing to mitigate the fuel inefficiencies and safety hazards arising from passenger payload uncertainty. This inquiry is of vital significance because traditional dispatch operations rely on static, standardized weight assumptions that prompt flight crews to carry excessive discretionary fuel, resulting in a severe cost-to-carry weight penalty and increased emissions. The empirical findings demonstrate that integrating physical load sensors with a microcontroller allows for the automatic, real-time capture of precise passenger weights, eliminating manual log discrepancies during boarding dispatches. Additionally, securely synchronizing these live payload measurements to a cloud database enables the automated calculation of center of gravity offsets and the seamless, instant generation of official flight loadsheets. Theoretically, these results shift the paradigm from static weight modeling to dynamic, hardware-to-cloud payload telemetry, establishing a continuous feedback loop between physical aircraft loading states and digital fuel-planning systems. Practically, general aviation operators and dispatchers must transition from standardized passenger manifests to sensor-verified loadsheets to eliminate payload uncertainty and optimize pre-flight fuel dispatches. To expand this research, the most critical next step is to integrate real-time engine thrust and en route wind telemetry into the cloud database architecture to calibrate the automatic fuel planning module under dynamic meteorological profiles.

Acknowledgement

This research was not funded by any grant.

References

- [1] A. N. Ahmad, "Arduino-Based Weight Detection for Aircraft Loading System," Final Year Project Report, Politeknik Sultan Azlan Shah, 2020.
- [2] M. H. Mansor, A. A. Rahman, and N. S. A. Halim, "Prototyping Load Measurement Using Microcontroller for Aviation Applications," *Journal of Embedded Systems*, vol. 8, no. 2, pp. 95–102, 2019.
- [3] A. Fernandez and S. Patel, "Automated Passenger Weight Telemetry and Microcontroller Systems in General Aviation," *Sensors*, vol. 21, no. 12, p. 4105, 2021, [doi: 10.3390/s21124105](https://doi.org/10.3390/s21124105).
- [4] L. Masiero, J. Zoltan, and R. Lobato, "Pay-per-weight air travel: Enhancing sustainability through voluntary weight disclosure," *Journal of Air Transport Management*, vol. 107, p. 102358, 2023, [doi: 10.1016/j.jairtraman.2023.102358](https://doi.org/10.1016/j.jairtraman.2023.102358).
- [5] D. Dalalah, M. T. Bataineh, and F. Alkhatib, "Passenger weight and airline overbooking optimization: A probabilistic approach," *Transport Policy*, vol. 116, pp. 91–99, 2022. [doi: 10.1016/j.tranpol.2021.11.012](https://doi.org/10.1016/j.tranpol.2021.11.012).
- [6] Baumann, S., T. Neidhardt, and U. Klingauf. "Evaluation of the aircraft fuel economy using advanced statistics and machine learning." *CEAS Aeronautical Journal* 12, no. 3 (2021): 669-681.
- [7] M. Z. Razak and N. A. Hamid, "Web-Based Dashboard for UAV Telemetry Data Monitoring," *International Journal of Computing and Engineering*, vol. 5, no. 1, pp. 17–24, 2021.
- [8] Huang, Chenyu, and Xiaoyue Cheng. "Estimation of aircraft fuel consumption by modeling flight data from avionics systems." *Journal of Air Transport Management* 99 (2022): 102181. [doi: 10.1016/j.jairtraman.2022.102181](https://doi.org/10.1016/j.jairtraman.2022.102181).
- [9] Jia, Chunchun, Wei Liu, K. T. Chau, Hongwen He, Jiaming Zhou, and Songyan Niu. "Passenger-aware reinforcement learning for efficient and robust energy management of fuel cell buses." *Etransportation* 27 (2026): 100537. [doi: 10.1016/j.etrans.2025.100537](https://doi.org/10.1016/j.etrans.2025.100537).
- [10] Pagoni, Ioanna, and Voula Psaraki-Kalouptsidi. "Calculation of aircraft fuel consumption and CO2 emissions based on path profile estimation by clustering and registration." *Transportation Research Part D: Transport and Environment* 54 (2017): 172-190. [doi: 10.1016/j.trd.2017.05.006](https://doi.org/10.1016/j.trd.2017.05.006).
- [11] Brueckner, Jan K., and Chrystiane Abreu. "Airline fuel usage and carbon emissions: Determining factors." *Journal of Air Transport Management* 62 (2017): 10-17. [doi: 10.1016/j.jairtraman.2017.01.004](https://doi.org/10.1016/j.jairtraman.2017.01.004).

- [12] Knacker, Tim, Till Dannewald, and Thomas Kirschstein. "Estimation of aircraft fuel consumption and emissions during taxiing processes." *Transportation Research Part D: Transport and Environment* 155 (2026): 105330. [doi: 10.1016/j.trd.2026.105330](https://doi.org/10.1016/j.trd.2026.105330).
- [13] Wandelt, Sebastian, Xiaoqian Sun, and Morton O'Kelly. "Drivers for fuel efficiency of passenger airlines: A worldwide study." *Journal of Air Transport Management* 137 (2026): 103093. [doi: 10.1016/j.jairtraman.2026.103093](https://doi.org/10.1016/j.jairtraman.2026.103093).
- [14] Yan, Mei, Runkun Chen, Hongwen He, Menglin Li, Yong Wang, Yunfei Bai, and Jingda Wu. "Enhancing energy management of fuel cell buses: An intelligent strategy for passenger load variation." *International Journal of Hydrogen Energy* 259 (2026): 156632. [doi: 10.1016/j.ijhydene.2026.156632](https://doi.org/10.1016/j.ijhydene.2026.156632).
- [15] Kang, Lei, and Mark Hansen. "Improving airline fuel efficiency via fuel burn prediction and uncertainty estimation." *Transportation Research Part C: Emerging Technologies* 97 (2018): 128-146. [doi: 10.1016/j.trc.2018.10.002](https://doi.org/10.1016/j.trc.2018.10.002).
- [16] Federal Aviation Administration, "Advisory Circular 120-27F – Aircraft Weight and Balance Control," U.S. Department of Transportation, 2020.
- [17] International Civil Aviation Organization, "Aircraft Weight and Balance Manual," 4th ed., 2017.
- [18] IEEE Aerospace and Electronic Systems Society, "IEEE Standard for Airborne Equipment Weight and Balance Measurement," vol. 20, no. 2, pp. 112–118, 20